

## Series 1000 Cooler Options

Lead Time	Cooler (Part Number Configurator: 1000)					
2 wks	<b>1040</b>	One 10" Heat Exchanger, (1) Active, (1) Sample Stream				
	<b>1050</b>	Two 10" Heat Exchangers, (1) Passive/(1) Active, (1) Sample Stream				
	<b>1060</b>	Two 10" Heat Exchangers, (2) Active, (1) Sample Stream				
	<b>1080</b>	Two 10" Heat Exchangers, (2) Active, (2) Sample Streams				
	<b>1090</b>	Four 10" Heat Exchangers, (2) Passive/(2) Active, (1) or (2) Sample Streams				
4 wks	<b>1390</b>	Three 10" Heat Exchangers, (3) Active, (1) or (3) Sample Streams				
	<b>1490</b>	Four 10" Heat Exchangers, (4) Active, (1), (2) or (4) Sample Streams				
<b>10" Heat Exchanger Material (Price per Heat Exchanger)</b>						
+1 wk	<b>SS</b>	316 Stainless Steel: (Inner and Outer)				
	<b>PV</b>	Glass/Kynar: (Kynar Inner/Glass Outer)				
	<b>C</b>	Hastelloy C276: (316SS Inner/C276 Outer)				
	<b>CC</b>	Hastelloy C276: (Inner and Outer)				
	<b>ST</b>	Teflon Coated 316 Stainless Steel				
	<b>SW</b>	316 Welded Stainless Steel: (High Pressure)				
	<b>SN</b>	SilcoNert™ 2000 coated 316 Stainless Steel				
	<b>KK</b>	Kynar/ Kynar: (Inner and Outer)				
	<b>N</b>	No Heat Exchangers Included				
	<b>Voltage &amp; Area Location Classification</b>					
<b>115</b>	115 VAC 50/60 Hz; General Purpose (GP) Area					
<b>230</b>	230 VAC 50/60 Hz; General Purpose (GP) Area					
<b>115HL</b>	115 VAC 50/60 Hz Class I, Div. 2 Hazardous Location (HL) (1090 Only)					
<b>230HL</b>	230 VAC 50/60 Hz Class I, Div. 2 Hazardous Location (HL) (1090 Only)					
<b>Stream Configuration</b>						
+1 wk	<b>DS</b>	Dual Sample Stream (Options for Models 1080 & 1090 only)				
	<b>TS</b>	Tri Stream Mode - 1390 Only				
	<b>QS</b>	Quad Stream Mode - 1490 Only				
	<b>N</b>	Single Sample Stream				
<b>Condensate Drain</b>						
+1 wk	<b>LD</b>	Liquid Drainer				
	<b>1040</b>	1040 Cooler - One Heat Exchanger				
	<b>1050, 1060 &amp; 1080</b>	1050, 1060 & 1080 Cooler - Two Heat Exchangers				
	<b>1390</b>	1390 Cooler - Three Heat Exchangers				
	<b>1090 &amp; 1490</b>	1090 & 1490 Cooler - Four Heat Exchangers				
	<b>A</b>	Aspirated Drainer				
	<b>1040</b>	1040 Cooler - One Heat Exchanger				
	<b>1050, 1060 &amp; 1080</b>	1050, 1060 & 1080 Cooler - Two Heat Exchangers				
	<b>1390</b>	1390 Cooler - Three Heat Exchangers				
	<b>1090 &amp; 1490</b>	1090 & 1490 Cooler - Four Heat Exchangers				
<b>N</b>	No Condensate Drain					
<b>Options (Select all that apply)</b>						
+1 wk	<b>TCK</b>	New Jersey Option - Type K T/C - Stand alone option				
	<b>TCJ</b>	New Jersey Option - Type J T/C - Stand alone option				
	<b>N</b>	No New Jersey Option				
	<b>SPE</b>	Stacked Peltier elements - Stand alone option				
	<b>N</b>	Standard Peltier Elements				
<b>1040</b>	<b>SS</b>	<b>-230</b>	<b>-N</b>	<b>-N</b>	<b>-N</b>	<b>-N</b>

\* Lead Times are not compounded. Lead time is Cooler + longest option.