

271 Gas Sample Probe for General Purpose Areas

271 Model Non-Heated Extractive Probe (Part Number Configurator: 271)	
All Sample Probes are Configured & Sold WITHOUT probe tubes (Stinger, Quill, Straw)	
271	316SS Probe w/ Sanitary Clamp
Flange Size (Other Sizes Available, Contact the Factory)	
F2	2" 150# RF Flange
F3	3" 150# RF Flange
F4	4" 150# RF Flange
Blowback Control	
24	24 VDC Solenoid
115	115 VAC Solenoid
230	230 VAC Solenoid
BBT115	115 VAC Powered Blowback w/Smart Timer
BBT230	230 VAC Powered Blowback w/Smart Timer
N	No Blowback Included
Enclosure Options (* Cannot be used in conjunction with Blowback Timer Card)	
FG	Fiberglass Enclosure (Standard)
FGI	Fiberglass Enclosure, Insulated
FGH115	Fiberglass Enclosure, Insulated/Heated, 115 VAC 50/60 Hz*
FGH230	Fiberglass Enclosure, Insulated/Heated, 230 VAC 50/60 Hz*
SS	Stainless Steel Enclosure
SSI	Stainless Steel Enclosure, Insulated
SSH115	Stainless Steel Enclosure, Insulated/Heated, 115 VAC 50/60 Hz*
SSH230	Stainless Steel Enclosure, Insulated/Heated, 230 VAC 50/60 Hz*
N	No Enclosure
Calibration Options	
CV	1/4" Cal Gas Inlet and Check Valve
N	No Cal Gas Inlet
271 -F2 -N -FG -N	

NOTE: Probe Tip Filters & Probe Tubes Purchased Separately.

Drawing: P1186