

## 500 Portable Series Cooler Integration Options

Lead Time	Cooler (Part Number Configurator: 500T)	
2 wks	<b>512</b>	One (1) Sample Point - One (1) Active 5" Heat Exchanger
	<b>513</b>	One (1) Sample Point - Two (2) Passive/Active 5" Heat Exchangers
	<b>514</b>	One (1) Sample Point - Two (2) Active/Active 5" Heat Exchangers
<b>5" Heat Exchanger) Material (Price per Heat Exchanger)</b>		
<b>SS</b> 316 Stainless Steel		
<b>PV</b> Glass/Kynar		
<b>C</b> Hastelloy C276		
+1 wk	<b>ST</b> Teflon Coated 316 Stainless Steel:	
	<b>SW</b>	316 Welded Stainless Steel: (High Pressure)
	<b>SN</b>	SilcoNert™ 2000 coated 316 Stainless Steel:
	<b>KK</b>	Kynar/ Kynar:
<b>Voltage</b>		
<b>115</b> 115 VAC 50/60 Hz; General Purpose (GP) Area		
<b>230</b> 230 VAC 50/60 Hz; General Purpose (GP) Area		
<b>Flow meter with 316SS Needle Valve</b>		
<b>FM5</b> 5.0 lpm		
<b>512 -PV -115 -FM5</b>		

\* Lead Times are not compounded. Lead time is Cooler + longest option.