

## Sample Conditioning Drawer - Configuration Options

Sample Conditioning Drawer Includes: Sample pump - Peristaltic Pump - Vacuum & Pressure Gauges - Vacuum & Pressure Switches - Analyzer/Bypass/Calibration Gas Flow Meters - Zero & Span Calibration Gas Solenoids & Calibration Gas Regulator

Lead Time	Integration Options	
<b>SCD</b>	<b>Sample Conditioning Drawer Integrated with accessories selected below</b>	
6 wks	<b>1570</b>	Cooler 5" Passive/Active (4 Heat Exchangers)
+2 Wks	<b>Heat Exchangers Material</b>	
	<b>SS</b>	316 Stainless Steel: (Inner and Outer)
	<b>PV</b>	Glass/Kynar: (Kynar Inner/Glass Outer)
	<b>C</b>	Hastelloy C-276: (316SS Inner/C-276 Outer)
	<b>CC</b>	Hastelloy C-276: (Inner and Outer)
	<b>ST</b>	Teflon coated 316 Stainless Steel: (Inner and Outer)
	<b>SW</b>	316 Welded Stainless Steel: (High Pressure)
	<b>SN</b>	SilcoNert™ 2000 coated 316 Stainless Steel:
	<b>KK</b>	Kynar/ Kynar: (Inner and Outer)
	<b>Voltage &amp; Area Location Classification</b>	
	<b>115</b>	115 VAC 50/60 Hz; General Purpose (GP) Area
	<b>230</b>	230 VAC 50/60 Hz; General Purpose (GP) Area
	<b>Sample Pump with pressure controller.</b>	
	<b>SP1</b>	Single Head Pump
	<b>SP2</b>	Dual Head Pump
<b>Calibration Gas Solenoids (Standard panel includes two Calibration Gas Solenoids)</b>		
<b>Cal2</b>	No Additional Calibration Gas Solenoids (Base Panel Includes 2)	
<b>Cal3</b>	1 Additional Calibration Gas Solenoid (3 Total)	
<b>Cal4</b>	2 Additional Calibration Gas Solenoid (4 Total)	
<b>Cal5</b>	3 Additional Calibration Gas Solenoid (5 Total)	
<b>Cal6</b>	4 Additional Calibration Gas Solenoid (6 Total)	
<b>Analyzer Flow Meter Options</b>		
<b>FM1</b>	1 Base Panel 2.5 LPM Flow Meter = Panel with 1 Analyzer Meter, 1 Bypass Meter, 1 Cal Gas Meter	
<b>FM2</b>	1 Additional 2.5 LPM Flow Meter = Panel with 2 Analyzer Meters, 1 Bypass Meter, 1 Cal Gas Meter	
<b>FM3</b>	2 Additional 2.5 LPM Flow Meter = Panel with 3 Analyzer Meters, 1 Bypass Meter, 1 Cal Gas Meter	
<b>FM4</b>	3 Additional 2.5 LPM Flow Meter = Panel with 4 Analyzer Meters, 1 Bypass Meter, 1 Cal Gas Meter	
<b>Heated Sample Line Control</b>		
<b>HSL</b>	DIN Controller Temperature 1/32 Watlow, SSR & Alarm Contact	
<b>N</b>	No Option Included	
<b>Toggle Panel (Manual Control)</b>		
<b>TGL</b>	Toggle Panel Direct/System Calibration - Up to 6 Calibration Gases	
<b>N</b>	No Option Included	
<b>Peristaltic Tubing Options</b>		
<b>PP1</b>	Phar-Med High Pressure Pump Tubing (\$81.93/head)	
<b>PP2</b>	Viton Pump Tubing (\$187.58/head)	
<b>PP3</b>	Tygon Fuel Grade Tubing (\$32.08/head)	
<b>PP4</b>	Norprene Tubing (\$81.93/head)	
<b>S</b>	Standard Tubing	
<b>SCD</b>	<b>-1570</b>	<b>-SS -115 -SP1 -Cal2 -FM1 -HSL -TGL -S</b>
← Standard Part Number		