

**SPARE PARTS RECOMMENDATIONS FOR MODEL 1221**

<b>Pneumatic Controlled Probes</b>	
<b>Part No.</b>	<b>Description</b>
3019-1019	Pressure Gauge 0-100psi Bottom Connect
3020-1008	Thermometer 3" dial 12" stem 0-200°F & -10 to 90°C 316SS
4954-1087	Bleed Tube 100 micron
4955-0090	Manual Valve 2 Way
4955-1137	Pneumatic Controller Valve
4955-1138	Check Valve @ 12psi
4955-1139	Air Relay
4955-1140	Air Actuated Toggle Valve
4960-1011	Vortex Tube Muffler Medium
4960-1013	Vortex Tube 40 SCFM
8200-1026	Pneumatic Timer
8200-1027	Regulator w/ Gauge 0-60 psi

<b>Remote Controlled Probes</b>	
<b>Part No.</b>	<b>Description</b>
1150-1049	RTD 6" Length 1/8" Dia Fiberglass Cable 36" Armor 316SS
1150-1050	RTD 1" Length 1/8" Dia Fiberglass Cable 36" Armor 316SS
1150-1051	RTD 10.5" Length 1/8" Dia Fiberglass Cable 18" Lead 316SS
1150-1052	RTD 1" Length 1/8" Dia Fiberglass Cable 12" Lead 316SS
4955-0109	Air Operated Toggle Valve - Normally Closed, 1/4" Tube
4955-0260	Solenoid Valve 3-Way 1/4" NPT SS 24VDC Explosion Proof
4955-1141	Solenoid Valve 2-Way 1/2" NPT Brass NC Explosion Proof
4960-1011	Vortex Tube Muffler Medium
4960-1013	Vortex Tube 40SCFM Medium

<b>Local Controlled Probes</b>	
<b>Part No.</b>	<b>Description</b>
1150-1049	RTD 6" Length 1/8" Dia Fiberglass Cable 36" Armor 316SS
1150-1050	RTD 1" Length 1/8" Dia Fiberglass Cable 36" Armor 316SS
1150-1051	RTD 10.5" Length 1/8" Dia Fiberglass Cable 18" Lead 316SS
1150-1052	RTD 1" Length 1/8" Dia PVC Cable 12" Lead 316SS
3152-1014	6A Relay with Fuse, C1D2
4955-0109	Air Operated Toggle Valve - Normally Closed, 1/4" Tube
4955-0260	Solenoid Valve 3-Way 1/4" NPT SS 24VDC Explosion Proof
4955-1141	Solenoid Valve 2-Way 1/2" NPT Brass NC Explosion Proof
4960-1011	Vortex Tube Muffler Medium
4960-1013	Vortex Tube 40SCFM Medium
5400-1019	Power Supply 24Vdc 60Watt 100-240Vac Input C1D2
5600-1251	PLC, FC6A Series 24Vdc C1D2
5600-1252	HMI for FC6A, C1D2
5600-1253	Analog Input Module, FC6A Series 4-CH (PT100) C1D2
5600-1267	SD Memory Card SDHC 32 GB Class 10