



**SPARE PARTS RECOMMENDATIONS FOR MODEL 275HD**

<b>Level A, Consumable Parts:</b>		
<b>Part No.</b>	<b>Description</b>	<b>2 Yr. Rec.</b>
4903-0001	Gasket Ring For 4" 150# Flange Garlock 9850 1/16" Thk	
4903-0003	Gasket Ring For 3" 150# Flange Garlock 9850 1/16" Thk	
4903-0004	Gasket Ring For 2" 150# Flange Garlock 9850 1/16" Thk	
4903-1035	Gasket for 4" 150# flange, silicone sponge style (red) use with HPA	
4903-1036	Gasket for 6" 150# flange, silicone sponge style (red) use with HPA	
4903-1000	Gasket, Silicon Foam Closed Cell HT-800 1/4" Thick for 275 Enclosure	
4903-1001	Gasket, 275 Subflange	
4904-0016	O-Ring 2-217 Viton	
4904-0036	O-Ring 2-318 Viton	
4904-0041	O-Ring 2-012 Viton	
4904-0046	O-Ring 2-110 Viton	
4904-1006	O-Ring 2-017 Viton	
4904-2001	O-Ring 2-217 Markez/Kalrez 7075 (70-80 Durometer)	
4904-2016	O-Ring 2-318 Markez/Kalrez 7075 (70-80 Durometer)	
4904-1007	O-Ring 2-012 Markez/Kalrez 7075 (70-80 Durometer)	
4904-2015	O-Ring 2-110 Markez/Kalrez 7075 (70-80 Durometer)	
4904-2001	O-Ring 2-217 Markez/Kalrez 7075 (70-80 Durometer)	
4980-0328	Filter Element: 316 Stainless Steel 2 Micron 9" 1/2" MNPT Connection	
8010-0011	Silicone Grease 1/4 Ounce package rated for 600F	
8010-1000	Capsule Vapor 2' Two Year Corrosion Protection	
9515-1000	Kit Lubricant Never Seez Heavy Metal Free for Severe Industrial Applications	
4980-1071	1 micron Quartz Wool 1/3 oz and container	

<b>Spare Parts</b>		
<b>Part No.</b>	<b>Description</b>	<b>2 Yr. Rec.</b>
5110-0015	Acid Blocker Assembly	
5209-0391	Dilution Critical Orifice #2 Standard Temperatures	
5209-0380	Dilution Critical Orifice #3 Standard Temperatures	
5209-0382	Dilution Critical Orifice #5 Standard Temperatures	
5209-0383	Dilution Critical Orifice #6 Standard Temperatures	
5209-0384	Dilution Critical Orifice #7 Standard Temperatures	
5209-0385	Dilution Critical Orifice #8 Standard Temperatures	
5209-0387	Dilution Critical Orifice #10 Standard Temperatures	
5209-0388	Dilution Critical Orifice #11 Standard Temperatures	
5209-0389	Dilution Critical Orifice #12 Standard Temperatures	
5209-0390	Dilution Critical Orifice #15 Standard Temperatures	
5209-1164	Dilution Critical Orifice #2 High Temperatures	
5209-1036	Dilution Critical Orifice #3 High Temperatures	
5209-1037	Dilution Critical Orifice #4 High Temperatures	
5209-1038	Dilution Critical Orifice #5 High Temperatures	
5209-1039	Dilution Critical Orifice #6 High Temperatures	
5209-1040	Dilution Critical Orifice #7 High Temperatures	
5209-1041	Dilution Critical Orifice #8 High Temperatures	
5209-1042	Dilution Critical Orifice #9 High Temperatures	
5209-1043	Dilution Critical Orifice #10 High Temperatures	
5209-1044	Dilution Critical Orifice #11 High Temperatures	
5209-1045	Critical Orifice Assy Bolt # 12 High Temperatures	
5209-1046	Critical Orifice Assy Bolt # 15 High Temperatures	

Continued on next page



5209-1000	Fast-Loop/Bypass Orifice Bolt Standard Temperatures	
5209-1061	Fast-Loop/Bypass Orifice Bolt High Temperatures	
5209-1002	Manifold, 275HD, SS, w/ Fittings, Use w/o HPA ***Does Not Include O-Rings***	
5209-1005	Assembly Filter and Cap for 275HD Chamber w/ Woven Filter SS	
5209-1014	275 Filter SQR Assembly w/ Woven Filter High Temp Temp.	
5209-1015	275 Filter Assembly w/ Woven Filter & C-276 Filter Holder	
5209-1016	275 Filter Assembly w/ Woven Filter, High Temp & C-276 Filter Holder	
4955-0136	Valve SV 120VAC 2Way High Flow	
4955-0137	Valve SV 2Way 24VDC High Flow	
4955-0141	Valve SV 2Way 230 VAC High Flow	
4955-0256	Valve Toggle Pneumatic Actuated Hi Flow NC	
4955-0148	Valve Check 1/4" Tube x 1/4" Tube 316SS Set At 3 PSI	
4956-1002	Accumulator, 7", with 3/8" stub tube mounting (with SW nut, ferrule)	
4956-0009	Accumulator, heated, 400 °F, for enclosed applications, 115/230 VAC, 1/4" MNPT	

<b>Optional Parts:</b>		
<b>Part No.</b>	<b>Description</b>	<b>2 Yr. Rec.</b>
8000-0016	Tape High Temperature Poly-Temp Nickel Anti-Seize 1/2" Wide	
8010-1000	Capsule Vapor 2' Two Year Corrosion Protection	
9506-1001	Cleaning Wire for Eductor and #15 Orifice 12 mil	
9506-1002	Brush, Flue Double Spiral High Carbon Steel	
9506-1005	Flue Brush Extension Handle 36"	
9506-1006	T Extension Flue Brush Handle	
3014-1001	Heater Element 3/8" OD x 11" long w/ 24" total lead length 800W 240 VAC .	
1150-1047	Sensor Thermocouple Type K 4" Sheath 3/16" Diameter 1/8" Mnpt Mount with 60"	
1150-1048	Sensor RTD PT100 4" Sheath 3/16" Diameter 1/8" Mnpt Mount with 60" Armor	
4704-1043	Screw machine Stainless Steel 10-32 x 1 1/2" Slotted Washer hex head	
5150-1022	Jacket Insulation 275HD	
3012-0005	Circuit Breaker Single Pole 10 Amp Din Rail Mounted	
3012-1000	Circuit Breaker Dual Pole 10 Amp Din Rail Mounted	
5600-0128	DIN Controller Temperature 1/32 Watlow, output for SSR & relay	